

TOSHIBA



End of Sales



S300 Pro Surveillance Hard Drives

Capture every detail

Toshiba S300 Pro Surveillance Hard Drive is designed and tested for 24/7 reliable surveillance, built for speed, capacity, and longer content retention. Capture and analyse every frame from up to 64 video cameras in high resolution with the S300 Pro. Space is important to continually capture a history of video evidence over a period of time. With up to 10 TB you get the capacity to record and play back the events in real-time in high resolution and with object identification and face recognition.



Use for

- Surveillance Digital Video Recorders (sDVR)
- Surveillance Network Video Recorders (sNVR)
- Hybrid sDVR (analog and IP)
- RAID Storage Arrays for Surveillance

Top Features

- Designed for 24/7 operation
- Up to 64 cameras
- Workload up to 180 TB/year
- MTTF/MTBF up to 1.0 million hours
- 7200 rpm speed with 256 MiB buffer
- CMR technology
- 3.5-inch Form Factor

Capacities

10 TB 8 TB 6 TB



S300 Pro

End of Sales

 Surveillance Hard Drives

Capacity *1	10 TB		8 TB		6 TB	
Parts Number	HDWT31AUZSVA		HDWT380UZSVA		HDWT360UZSVA	
Basic Specifications						
Recording Technology	CMR					
Interface	SATA 6.0 Gbit/s					
Mechanical Design	Air					
Form Factor *2	3.5-inch					
Sector Size	512e					
Features						
Number of Camera *3	up to 64					
Drive Bays Supported	8+					
24 / 7 Operation	yes					
Rotational Vibration Safeguard (RVS)	yes					
Shock Sensor	yes					
Performances						
Rotation Speed	7200 rpm					
Sustained data transfer rate *4	248 MB/s (237 MiB/s)		241 MB/s (230 MiB/s)			
Buffer Size *5	256 MiB					
Reliability						
MTTF/MTBF *6	1 000 000 hours					
Unrecoverable Error Rate	1 per 10E14					
Maximum rated workload *7	180 TB/year					
Load/Unload cycles	600 000 times					
Power Requirements						
Supply Voltage	12 VDC ±10 % 5 VDC +6 / -5 %					
Power Consumption	Operating	9.48 W		8.61 W		7.88 W
	Active Idle	7.15 W		6.33 W		5.59 W
Environmental						
Temperature	Operating *8	0 to 70 °C (Surface)				
	Non-operating	-40 to 70 °C				
Vibration	Operating	7.35 m/s ² {0.75 G} (5 to 300 Hz) 2.45 m/s ² {0.25 G} (300 to 500 Hz)				
	Non-operating	29.4 m/s ² {3.0 G} (5 to 500 Hz)				
Shock	Operating	686 m/s ² {70 G} (2 ms duration)				
	Non-operating	2450 m/s ² {250 G} (2 ms duration)				
Acoustics (Active Idle)	34 dB (Typ.)					
Physical						
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm (Max)					
Weight	770 g (Max)					

*1 Definition of capacity: One terabyte (TB) = one trillion bytes, but storage capacity actually available may vary depending on operating environment and formatting. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

*2 "3.5-inch" means the form factor of HDDs. They do not indicate drive's physical size.

*3 Number of surveillance cameras support capability is defined by performance simulation with High Definition cameras at 10Mbit/s rate. Actual results may vary based on various factors, including the types of cameras installed, the system's hardware and software capabilities, and the video compression technology used, as well as system variables such as resolution, frames per second, and other settings.

*4 Read and write speed may vary depending on the host device, read and write conditions, and file size.

*5 A mebibyte (MiB) means 1 048 576 bytes.

*6 MTTF/MTBF (Mean Time to Failure/Mean Time Between Failures) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF/MTBF.

*7 Workload is a measure of the data throughput of the year, and it is defined as the amount of data written, read or verified by commands from the host system.

*8 Operation of high surface temperature will be shortened of the drives useful life. The recommendation operating condition of surface temperature is less than 60°C.

- Product image may represent a design model.
- Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant information of this document and the instructions for the application that Product will be used with or for.