

## MN SERIES (Helium-sealed design) NAS HDD

End of Sales

Toshiba's MN series of 3.5-inch<sup>[1]</sup> 7200 rpm Helium-sealed hard disk drives (HDD) deliver up to 16 TB<sup>[2]</sup> of storage capacity, making it suitable for NAS applications that value high-capacity and optimal power efficiency. To address NAS-class requirements, the MN series provide an up to 1 200 000 hour MTTF<sup>[3]</sup>, 180 TB/year workload<sup>[4]</sup> rating and support 24/7 power-on operation. The MN series also feature vibration compensation technology to help deliver consistent performance in up to 8 drive bay storage enclosures.



Product image may represent a design model.

### KEY FEATURES

- 16 TB Capacity (14 and 12TB model also available)
- 7200 rpm Performance
- SATA 6.0 Gbit/s Interface<sup>[5][6]</sup>
- 180 total TB Transferred per Year Workload Rating
- Rotational Vibration (RV) Sensors for Great Scalability and Good Performance
- 24/7 operation

### APPLICATIONS

- Branch-office / Remote-office Networked File Storage
- File and Object storage solutions
- Archiving and data back-up
- Consumer NAS file storage
- Private cloud storage

### SPECIFICATIONS

| Item                                       |  | MN08ACA16T   | MN07ACA14T   | MN07ACA12T |
|--|--|--|--|------------|
| Interface                                  |  | SATA-3.3   |  |            |
| Formatted Capacity                         |  | 16 TB  | 14 TB  | 12 TB      |
| Performance                                | Interface Speed                            | 6.0 Gbit/s, 3.0 Gbit/s, 1.5 Gbit/s                                       |  |            |
|  | Rotation Speed                             | 7200 rpm   |  |            |
|  | Buffer Size                                | 512 MiB <sup>[6]</sup>   | 256 MiB  |            |
|  | Max Data Transfer Speed (Sustained) (Typ.) | 262 MiB/s  | 248 MiB/s  | 242 MiB/s  |
| Logical Data Block Length                  |  | HOST: 512 B, DISK: 4096 B <sup>[7]</sup>                                 |  |            |
| Supply Voltage                             | Allowable Voltage                          | 12 V <sup>[8]</sup> ± 10 %<br>5 V <sup>[8]</sup> +10% -7% <sup>[9]</sup> | 12 V <sup>[8]</sup> ± 10 %<br>5 V <sup>[8]</sup> ± 5% <sup>[9]</sup> |            |
| Power Consumption                          | Operating <sup>[10]</sup> (Typ.)           | 6.91 W   | 6.77 W   | 6.49 W     |
|  | Active Idle (Typ.)                         | 4.03 W   | 4.54 W   | 4.28 W     |
| Acoustics <sup>[11]</sup><br>(Sound Power) | Active Idle (Typ.)                         | 20 dB  |  |            |
|  | Seek (Typ.)                                | 32 dB  | 35 dB  |            |

## ENVIRONMENTAL LIMITS

| Item                      |                               | MN08ACA16T   | MN07ACA14T<br>MN07ACA12T                           |
|---------------------------|-------------------------------|--|--|
| Temperature               | Operating (surface)           | 0 °C to 65 °C (No condensation)  | 5 °C to 60 °C (No condensation)                    |
|                           | Non-Operating (ambient)       | - 40 °C to 70 °C <sup>[15]</sup><br>(No condensation)  | - 40 °C to 70 °C <sup>[15]</sup> (No condensation) |
|                           | Storage condition & Period    | 0 °C to 70 °C (No condensation)  |  |
|                           |                               | 6 months within shipping package   |  |
| Humidity                  | Operating                     | 5 % to 90 % R.H. (No condensation)   |  |
|                           | Non-Operating                 | 5 % to 95 % R.H. (No condensation)   |  |
| Shock                     | Operating                     | 686 m/s <sup>2</sup> { 70 G } ( 2 ms duration )  |  |
|                           | Non-Operating                 | 2450 m/s <sup>2</sup> { 250 G } ( 2 ms duration )  |  |
| Vibration <sup>[12]</sup> | Operating <sup>[13]</sup>     | 7.35 m/s <sup>2</sup> { 0.75 G } ( 5 to 300 Hz )<br>2.45 m/s <sup>2</sup> { 0.25 G } (300 to 500 Hz) |  |
|                           | Non-Operating <sup>[14]</sup> | 29.4 m/s <sup>2</sup> { 3.0 G } ( 5 to 500 Hz )  |  |
| Altitude                  | Operating                     | - 305 m to 3048 m (No condensation)<br>(5 °C to 55 °C ambient)                                       |  |
|                           | Non-Operating                 | - 305 m to 12 192 m <sup>[15]</sup> (No condensation)  |  |

## RELIABILITY

| Item  | MN08ACA16T                             | MN07ACA14T<br>MN07ACA12T |
|---|--|--------------------------|
| MTTF  | 1 200 000 h                            | 1 000 000 h              |
| Non-recoverable Error Rate                                    | 1 error per 10 <sup>14</sup> bits read |                          |
| Load / Unload   | 300 000 times                          |                          |
| Availability  | 24 hours/day, 7 days/week              |                          |
| Rated Annual Workload<br>(Total TB Transferred per Year, R/W) | 180 TB/year                            |                          |

## MECHANICAL SPECIFICATIONS

| Item   | Specification |
|--------|---------------|
| Width  | 101.85 mm Max |
| Height | 26.1 mm Max   |
| Length | 147.0 mm Max  |
| Weight | 720 g Max     |

[1] "3.5-inch" mean the form factor of HDDs. They do not indicate drive's physical size.

[2] Definition of capacity: Toshiba defines a terabyte (TB) as 1 000 000 000 000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1TB = 2<sup>40</sup> = 1 099 511 627 776 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

[3] MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

[4] Workload is defined as the amount of data written, read or verified by commands from host system.

[5] Read and write speed may vary depending on the host device, read and write conditions, and file size.

[6] A mebibyte (MiB) means 2<sup>20</sup>, or 1 048 576 bytes, and a gibibyte (GiB) means 2<sup>30</sup>, or 1 073 741 824 bytes.

[7] Read-modify-write is supported.

[8] Input voltages are specified at the HDD connector side, during HDD ready state.

[9] Make sure the value is not less than -0.3V DC (less than -0.6V, 0.1ms) when turning on or off the power.

[10] Operating watt is measured using 80% random read/write and 20% performance idle.

[11] The measuring method is based on ISO 7779.

[12] Vibration applied to the HDD is measured at near the mounting screw hole on the frame as much as possible.

[13] At random seek write/read and default on retry setting with log sweep vibration.

[14] At power-off state after installation.

[15] The range of altitude is 3048 m or less. Up to 55 °C at 7620 m. Up to 40 °C at 12 192 m.

\* Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant information of this document and the instructions for the application that Product will be used with or for.

\* Company names, product names, and service names may be trademarks of their respective companies.