

DT01ABAxxxV SERIES VIDEO STREAM HDD



Product image may represent a design model.

KEY FEATURES

- Up to 3 TB of Storage Capacity
- 24/7 operation
- Annual workload rating of 72 TB/year
- 3.5-inch Form Factor
- 5940 / 5700 rpm
- SATA up to 6.0 Gbit/s
- Advanced Format (AF) 512e Sector Length

APPLICATIONS

- Video Editing Systems
- Set-Top-Box (STB)
- Digital Video Recorders (DVR)
- Network Video Recorders (NVR)

SPECIFICATIONS

Item		DT01ABA300V	DT01ABA200V	DT01ABA100V	DT01ABA050V
Interface		Serial ATA 3.0 / ATA-8 (6.0 Gbit/s , 3.0 Gbit/s , 1.5 Gbit/s)			
Formatted Capacity		3 TB	2 TB	1 TB	500 GB
Performance	Interface Speed (Max)	6.0 Gbit/s			
	Rotation Speed	5940 rpm	5700 rpm		
	Average Latency Time	5.06 ms	5.27 ms		
	Buffer Size	32 MiB			
Logical Data Block Length		HOST: 512 B, DISK: 4096 B			
Supply Voltage	Allowable Voltage	12 V ± 10 % / 5 V ± 5 %			
Power Consumption	Read / Write (Typ.)	5.4 W	4.7 W	5.7 W	
	Low Power idle (Typ.)	4.2 W	3.3 W	3.0 W	
Acoustics (Sound Power)	Idle	24 dB	22 dB	19 dB	
	Seek	25 dB	24 dB	22 dB	

RELIABILITY

Model Number	DT01ABAxxxV
Non-recoverable Error Rate	1 error per 10 ¹⁴ bits read
MTBF	1 000 000 hours

MECHANICAL SPECIFICATIONS

Item	DT01ABA300V	DT01ABA200V	DT01ABA100V	DT01ABA050V
Height (Max)	26.1 mm			
Width	101.6 mm			
Length (Max)	147 mm			
Weight (Max)	680 g		450 g	

ENVIRONMENTAL LIMITS

Item	Specification	
Temperature	Operating	0 °C to 60 °C (No condensation)
	Non-Operating	- 40 °C to 70 °C (No condensation)
Humidity	Operating	8 % to 90 % R.H. (No condensation)
	Non-Operating	5 % to 95 % R.H. (No condensation)
Shock	Operating	686 m/s ² { 70 G } (2 ms duration)
	Non-Operating	2940 m/s ² { 300 G } (2 ms half size wave) 3430 m/s ² { 350 G } (2 ms half size wave)
Vibration	Operating	6.57 m/s ² { 0.67 G } (5 to 500 Hz)
	Non-Operating	10.2 m/s ² { 1.04 G } (2 to 200 Hz)
Altitude	Operating	- 300 m to 3048 m
	Non-Operating	- 300 m to 12 000 m

ENVIRONMENTAL FEATURE

Model Number	DT01ABAxV
RoHS	Compatible

Definition of capacity: Toshiba defines a megabyte (MB) as 1 000 000 bytes, a gigabyte (GB) as 1 000 000 000 bytes and a terabyte (TB) as 1 000 000 000 000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2³⁰ = 1 073 741 824 bytes and therefore shows less storage capacity.

Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

A kibibyte (KiB) means 2¹⁰, or 1024 bytes, a mebibyte (MiB) means 2²⁰, or 1 048 576 bytes, and a gibibyte (GiB) means 2³⁰, or 1 073 741 824 bytes.

MTBF (Mean Time Between Failure) of the HDDs during its life time is 1 000 000 hours. Average HDA surface temperature: 40 °C or less. Continual or sustained operation at case HDA surface temperature above 40 °C may degrade product reliability.

Toshiba Electronic Devices & Storage Corporation defines "RoHS-Compatible" products as products that either (i) contain no more than a maximum concentration value of 0.1% by weight in Homogeneous Materials for lead, mercury, hexavalent chromium, polybrominated biphenyls (PBBs) and polybrominated diphenyl ethers (PBDEs) and of 0.01% by weight in Homogeneous Materials for cadmium; or (ii) fall within any of the application exemptions set forth in the Annex to the RoHS Directive (Directive 2011/65/EC of the European Parliament and of the Council of 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment). "Homogeneous Material" means a material of uniform composition that cannot be mechanically disjoined (meaning separated, in principle, by mechanical actions such as unscrewing, cutting, crushing, grinding and/or abrasive processes) into different materials. Examples of "Homogeneous Materials" would be individual types of plastics, ceramics, glass, metals, alloys, paper, board, resins and coatings.

Read and write speed may vary depending on the host device, read and write conditions, and file size.

3.5-inch" mean the form factor of HDDs. They do not indicate drive's physical size.

Workload is a measure of the data throughput of the year, and it is defined as the amount of data written, read or verified by commands from the host system.

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, lifesaving and/or life supporting medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, and devices related to power plant. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Product may include products subject to foreign exchange and foreign trade control laws.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

Toshiba Electronic Devices & Storage Corporation

<https://toshiba.semicon-storage.com/>