

# TOSHIBA



## S300 AI Surveillance Hard Drives

### For Various Streams

S300 AI HDD, powered by OptiFrame™ AI technology, is optimized for AI workloads, enabling fast video data access for real-time analytics. Supporting up to 64 camera and 32 AI streams, it offers scalable performance for modern surveillance. With 550 TB/year workload and up to 2.5 million hours MTTF, it ensures 24/7 reliability in critical environments.

## OptiFrame™ AI



### Use for

- AI Video Analytics Server and Storage Systems
- Centralized Surveillance Data Storage Systems
- Video Archive and Data Recovery Systems
- Multi-Bay-RAID Storage for Surveillance Data

### Top Features

- Designed for 24/7 operation
- Up to 32 AI Streams
- Up to 64 cameras
- Workload 550 TB/year
- MTTF/MTBF up to 2.5 million hours
- 7200 rpm speed with up to 1024 MiB buffer
- CMR technology
- 3.5-inch Form Factor

### Capacities

24 TB	22 TB	20 TB	18 TB
16 TB	14 TB	10 TB	8 TB



S300 AI

 Surveillance Hard Drives

Capacity *1	24TB	22TB	20TB	18TB	16TB	14TB	10TB	8TB
Parts Number	MG11ACA24TE-V	MG11ACA22TE-V	MG11ACA20TE-V	MG11ACA18TE-V	MG11ACA16TE-V	MG11ACA14TE-V	MG10ADA10TE-V	MG10ADA800E-V
Basic Specifications								
Recording Technology	CMR							
Mechanical Design	He						Air	
Interface	SATA 6 Gbit/s							
Form Factor *2	3.5-inch							
Sector Size	512e							
Features								
AI Streams	up to 32							
Number of Camera *3	up to 64							
Drive Bays Supported	up to 24							
Tarnish resistant	yes							
24 / 7 Operation	yes							
Rotational Vibration Safeguard (RVS)	yes							
Shock Sensor	yes							
Performances								
Rotation Speed	7200 rpm							
Sustained data transfer rate *4	309 MB/s (295 MiB/s)	299 MB/s (285 MiB/s)	295 MB/s (281 MiB/s)				281 MB/s (268 MiB/s)	
Buffer Size *5	1024 MiB						512 MiB	
Reliability								
MTTF/MTBF *6	2 500 000 hours						2 000 000 hours	
Unrecoverable Error Rate	10 per 10 <sup>16</sup>							
Maximum rated workload *7	550 TB/year							
Load/Unload cycles	600 000 times							
Power Requirements								
Supply Voltage	12 V ±10 %, 5 V +10/-7 %							
Power Consumption	Operating	8.11 W		7.89 W	7.41 W		9.63 W	
	Active Idle	4.35 W		4.16 W	3.66 W		5.74 W	
Environmental								
Temperature	Operating *8	5 to 60 °C (Surface)						
	Non-operating	-40 to 70 °C						
Vibration	Operating	7.35 m/s <sup>2</sup> {0.75 G} (5 to 300 Hz) 2.45 m/s <sup>2</sup> {0.25 G} (300 to 500 Hz)						
	Non-operating	29.4 m/s <sup>2</sup> {3.0 G} (5 to 500 Hz)						
Shock	Operating	490 m/s <sup>2</sup> {50 G} (2 ms duration)					686 m/s <sup>2</sup> {70 G} (2 ms duration)	
	Non-operating	1960 m/s <sup>2</sup> {200 G} (2 ms duration)					2450 m/s <sup>2</sup> {250 G} (2 ms duration)	
Acoustics (Active Idle)	20 dB (Typ)						34 dB (Typ)	
Physical								
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm (Max)							
Weight	730 g (Max)						755 g (Max)	

\*1 Definition of capacity: One terabyte (TB) = one trillion bytes, but storage capacity actually available may vary depending on operating environment and formatting. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

\*2 "3.5-inch" means the form factor of HDDs. They do not indicate drive's physical size.

\*3 Number of surveillance cameras support capability is defined by performance simulation with High Definition cameras at 10Mbit/s rate. Actual results may vary based on various factors, including the types of cameras installed, the system's hardware and software capabilities, and the video compression technology used, as well as system variables such as resolution, frames per second, and other settings.

\*4 Read and write speed may vary depending on the host device, read and write conditions, and file size.

\*5 A mebibyte (MiB) means 1 048 576 bytes.

\*6 MTTF/MTBF (Mean Time to Failure/Mean Time Between Failures) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF/MTBF.

\*7 Workload is a measure of the data throughput of the year, and it is defined as the amount of data written, read or verified by commands from the host system.

\*8 Operation of high surface temperature will be shortened of the drives useful life. The recommendation operating condition of surface temperature is less than 60°C.

- Product image may represent a design model.
- Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant information of this document and the instructions for the application that Product will be used with or for.