# **TOSHIBA**

# RD Number: RD139

# RD Title: TB67S141NG Evaluation circuit BOM

Item No.	Designator	Quantity	Value	Part Number	Manufacturer	Description	Package	Not Mount
1	CVCC	1	0.1µF 100V	-	-	Chip capacitor	3.2mmX1.6mm	
2	CVREF	1	0.1µF 100V	-	-	Chip capacitor	3.2mmX1.6mm	
3	CVM2	1	0.1µF 100V	-	-	Chip capacitor	3.2mmX1.6mm	
4	CVM1	1	100µF 50V	-	-	Electrolytic capacitor		
5	CVDD	1	10µF 50V	-	-	Electrolytic capacitor		
6	RERR	1	10kΩ 0.25W	-	—	Chip resistor	3.2mmX1.6mm	
7	RALM	1	10kΩ 0.25W	-	-	Chip resistor	3.2mmX1.6mm	
8	RMO	0	10kΩ 0.25W	-	-	Chip resistor	3.2mmX1.6mm	√
9	ROSCM	0	10kΩ 0.25W	-	-	Chip resistor	3.2mmX1.6mm	√
10	ROSCM	1	10kΩ 0.25W	-	-	Leaded resistor		
11	ROSCM	2	Socket pin	-	-	Socket pin		
12	RVF1	0	2.5kΩ 0.125W	-	-	Leaded resistor		√
13	RVF1	2	Socket pin	-	-	Socket pin		
14	RVF2	0	2.5kΩ 0.125W	-	—	Leaded resistor		√
15	RVF2	2	Socket pin	-	-	Socket pin		
16	ZD1	1	CMZ36	CMZ36(TE12L.Q)	TOSHIBA	Zener diode	M-FLAT	
17	ZD2	0	Not mount	-	-	Zener diode		√
18	ZD3	0	Not mount	-	-	Zener diode		√
19	PHASEA	0	Pin header 3P	-	—	Jumper	2.54mm pitch	√
20		0	Jumper socket	-	-	Short pin	2.54mm pitch	√
21	PHASEB	0	Pin header 3P	-	-	Jumper	2.54mm pitch	√
22		0	Jumper socket	-	-	Short pin	2.54mm pitch	√
23	INA1	1	Pin header 3P	-	-	Jumper	2.54mm pitch	
24		1	Jumper socket	—	-	Short pin	2.54mm pitch	
25	INA2	1	Pin header 3P	—	-	Jumper	2.54mm pitch	
26		1	Jumper socket	—	-	Short pin	2.54mm pitch	

27	INB1	1	Pin header 3P	-	_	Jumper	2.54mm pitch	
28		1	Jumper socket	-	-	Short pin	2.54mm pitch	
29	INB2	1	Pin header 3P	-	-	Jumper	2.54mm pitch	
30		1	Jumper socket	-	-	Short pin	2.54mm pitch	
31	STBY	1	Pin header 3P	-	-	Jumper	2.54mm pitch	
32		1	Jumper socket	-	-	Short pin	2.54mm pitch	
33	BRAKE	1	Pin header 3P	-	-	Jumper	2.54mm pitch	
34		1	Jumper socket	-	-	Short pin	2.54mm pitch	
35	JP_VCC	1	Pin header 2P	-	-	Jumper	2.54mm pitch	
36		1	Jumper socket	-	-	Short pin	2.54mm pitch	
37	VDD	1	Check terminal	-	-	Logic pin		
38	VM	1	Check terminal	-	-	Logic pin		
39	VCC	1	Check terminal	-	-	Logic pin		
40	ERR	1	Check terminal	-	-	Logic pin		
41	ALM	1	Check terminal	-	-	Logic pin		
42	PHASEA	1	Check terminal	-	-	Logic pin		
43	PHASEB	1	Check terminal	-	-	Logic pin		
44	INA1	1	Check terminal	-	-	Logic pin		
45	INA2	1	Check terminal	-	-	Logic pin		
46	INB1	1	Check terminal	-	—	Logic pin		
47	INB2	1	Check terminal	_	—	Logic pin		
48	STBY	1	Check terminal	_	—	Logic pin		
49	BRAKE	1	Check terminal	_	—	Logic pin		
50	VREF	1	Check terminal	-	_	Logic pin		
51	VCOM	0	Check terminal	_	—	Logic pin		$\checkmark$
52	OUT_A+	1	Check terminal	_	—	Logic pin		
53	OUT_A-	1	Check terminal	-	-	Logic pin		
54	OUT_B-	1	Check terminal	-	-	Logic pin		
55	OUT_B+	1	Check terminal	_	-	Logic pin		
56	GND1	1	Check terminal	-	-	Logic pin		
57	GND2	1	Check terminal	-	-	Logic pin		
58	GND3	1	Check terminal	_	-	Logic pin		
59	GND4	1	Check terminal	-	_	Logic pin		
60	GND5	1	Check terminal	-	-	Logic pin		

61	CNA	1	Terminal block 2P	-	_	Terminal block		
62	CNB	1	Terminal block 2P	-	_	Terminal block		
63	CNV	1	Terminal block 2P	-	_	Terminal block		
64	IC1	1	TB67S141NG	TB67S141NG	TOSHIBA	Motor driver IC	SDIP24	

### **Terms of Use**

This terms of use is made between Toshiba Electronic Devices and Storage Corporation ("We") and customers who use documents and data that are consulted to design electronics applications on which our semiconductor devices are mounted ("this Reference Design"). Customers shall comply with this terms of use. Please note that it is assumed that customers agree to any and all this terms of use if customers download this Reference Design. We may, at its sole and exclusive discretion, change, alter, modify, add, and/or remove any part of this terms of use at any time without any prior notice. We may terminate this terms of use at any time and for any reason. Upon termination of this terms of use, customers shall destroy this Reference Design. In the event of any breach thereof by customers, customers shall destroy this Reference Design, and furnish us a written confirmation to prove such destruction.

#### 1. Restrictions on usage

1. This Reference Design is provided solely as reference data for designing electronics applications. Customers shall not use this Reference Design for any other purpose, including without limitation, verification of reliability.

2. This Reference Design is for customer's own use and not for sale, lease or other transfer.

3. Customers shall not use this Reference Design for evaluation in high or low temperature, high humidity, or high electromagnetic environments.

4. This Reference Design shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.

#### 2. Limitations

 We reserve the right to make changes to this Reference Design without notice.
This Reference Design should be treated as a reference only. We are not responsible for any incorrect or incomplete data and information.

3. Semiconductor devices can malfunction or fail. When designing electronics applications by referring to this Reference Design, customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of semiconductor devices could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Customers must also

refer to and comply with the latest versions of all relevant our information, including without limitation, specifications, data sheets and application notes for semiconductor devices, as well as the precautions and conditions set forth in the "Semiconductor Reliability Handbook".

4. When designing electronics applications by referring to this Reference Design, customers must evaluate the whole system adequately. Customers are solely responsible for all aspects of their own product design or applications. WE ASSUME NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.

5. No responsibility is assumed by us for any infringement of patents or any other intellectual property rights of third parties that may result from the use of this Reference Design. No license to any intellectual property right is granted by this terms of use, whether express or implied, by estoppel or otherwise.

6. THIS REFERENCE DESIGN IS PROVIDED "AS IS". WE (a) ASSUME NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (b) DISCLAIM ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO THIS REFERENCE DESIGN, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.

#### 3. Export Control

Customers shall not use or otherwise make available this Reference Design for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). This Reference Design may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of this Reference Design are strictly prohibited except in compliance with all applicable export laws and regulations.

## 4. Governing Laws

This terms of use shall be governed and construed by laws of Japan.