TOSHIBA

© 2020 Toshiba Electronic Devices & Storage Corporation

2020-05-07 Rev.2.0

RD Number: RD132

RD Title: TB6600FG Evaluation circuit BOM

Item No.	Designator	Quantity	Value	Part Number	Manufacturer	Description	Package	Not Mount
1	C_VREG	1	0.1µF 25V	—	—	Chip capacitor		
2	C_VCC2	1	0.1µF 50V	—	—	Chip capacitor		
3	C_VRF	1	0.1µF 25V	—	—	Chip capacitor		
4	C_VCC1	1	100µF 50V	—	—	Electrolytic capacitor		
5	C_VDD	0	10µF 25V	—	—	Electrolytic capacitor		√
6	C_02B	0	Not mount	—	—	Chip capacitor		√
7	C_01B	0	Not mount	—	—	Chip capacitor		✓
8	C_02A	0	Not mount	—	—	Chip capacitor		✓
9	C_01A	0	Not mount	—	—	Chip capacitor		✓
10	CON1	1	Connector	—	—	Connector 4P 2.5		
11	OUT2B	1	Check terminal	—	—	Logic pin		
12	OUT1B	1	Check terminal	—	—	Logic pin		
13	OUT2A	1	Check terminal	—	—	Logic pin		
14	OUT1A	1	Check terminal	—	—	Logic pin		
15	NFA	0	Check terminal	—	_	Logic pin		√
16	NFB	0	Check terminal	—	_	Logic pin		√
17	VREG	1	Check terminal	—	—	Logic pin		
18	VDD	1	Check terminal	—	—	Logic pin		
19	VCC	1	Check terminal	—	—	Logic pin		
20	ALERT	1	Check terminal	—	—	Logic pin		
21	TQ	1	Check terminal	—	—	Logic pin		
22	Latch/Auto	1	Check terminal	—	—	Logic pin		
23	VREF	1	Check terminal	-	_	Logic pin		
24	M1	1	Check terminal	_	_	Logic pin		
25	M2	1	Check terminal	_	_	Logic pin		
26	М3	1	Check terminal	_	_	Logic pin		

27	ENABLE	1	Check terminal	_	_	Logic pin		
28	RESET	1	Check terminal	_	_	Logic pin		
29	CLK	1	Check terminal	_	_	Logic pin		
30	CW/CCW	1	Check terminal	_	_	Logic pin		
31	OSC	1	Check terminal	_	_	Logic pin		
32	MO	1	Check terminal	_	_	Logic pin		
33	GND1	1	Check terminal	_	_	Logic pin		
34	GND2	1	Check terminal	_	_	Logic pin		
35	GND3	1	Check terminal	_	_	Logic pin		
36	GND4	1	Check terminal	_	_	Logic pin		
37	GND5	1	Check terminal	_	_	Logic pin		
38	GND6	1	Check terminal	_	_	Logic pin		
39	GND7	1	Check terminal	_	_	Logic pin		
40	JP_VREG	1	Pin header 2P	_	_	Jumper	2.54mm pitch	
41		1	Jump socket	_	_	Short pin	2.54mm pitch	
42	R_ALERT	1	100kΩ 0.25W	_	_	Leaded resistor	2.54mm pitch	
43	R_MO	1	100kΩ 0.25W	_	_	Leaded resistor	2.54mm pitch	
44	R_OSC	2	Socket pin	—	—	Socket pin		
45		1	51kΩ 0.25W	—	_	Leaded resistor	2.54mm pitch	
46		0	51kΩ 0.25W	—	—	Chip resistor	3.2mm×1.6mm	\checkmark
47	R_VRF1	2	Socket pin	_	—	Socket pin		
48		0	Not mount	—	_	Leaded resistor	2.54mm pitch	\checkmark
49	R_VRF2	2	Socket pin	—	_	Socket pin		
50		0	Not mount	_	_	Leaded resistor	2.54mm pitch	√
51	RRSA	1	0.22Ω 1W	—	—	Chip resistor	5.0mm×2.5mm	
52		0	0.22Ω 1W	—	—	Leaded resistor	2.54mm pitch	√
53	RRSB	1	0.22Ω 1W	—	—	Chip resistor	5.0mm×2.5mm	
54		0	0.22Ω 1W	_	_	Leaded resistor	2.54mm pitch	\checkmark
55	SW TQ	1	Pin header 3P	_	_	Jumper	2.54mm pitch	
56		1	Jump socket	_	_	Short pin	2.54mm pitch	
57	SW Latch/Auto	1	Pin header 3P	_	_	Jumper	2.54mm pitch	
58		1	Jump socket	—	—	Short pin	2.54mm pitch	
59	SW M1	1	Pin header 3P	—	—	Jumper	2.54mm pitch	
60		1	Jump socket	_	_	Short pin	2.54mm pitch	

61	SW M2	1	Pin header 3P	—	—	Jumper	2.54mm pitch
62		1	Jump socket	—	—	Short pin	2.54mm pitch
63	SW M3	1	Pin header 3P	-	—	Jumper	2.54mm pitch
64		1	Jump socket	-	—	Short pin	2.54mm pitch
65	SW ENABLE	1	Pin header 3P	—	—	Jumper	2.54mm pitch
66		1	Jump socket	-	—	Short pin	2.54mm pitch
67	SW RESET	1	Pin header 3P	—	—	Jumper	2.54mm pitch
68		1	Jump socket	—	—	Short pin	2.54mm pitch
69	SW CW/CCW	1	Pin header 3P	—	—	Jumper	2.54mm pitch
70		1	Jump socket	—	—	Short pin	2.54mm pitch
71	IC1	1	TB6600FG	TB6600FG	TOSHIBA	Motor driver IC	HQFP64

Terms of Use

This terms of use is made between Toshiba Electronic Devices and Storage Corporation ("We") and customers who use documents and data that are consulted to design electronics applications on which our semiconductor devices are mounted ("this Reference Design"). Customers shall comply with this terms of use. Please note that it is assumed that customers agree to any and all this terms of use if customers download this Reference Design. We may, at its sole and exclusive discretion, change, alter, modify, add, and/or remove any part of this terms of use at any time without any prior notice. We may terminate this terms of use at any time and for any reason. Upon termination of this terms of use, customers shall destroy this Reference Design. In the event of any breach thereof by customers, customers shall destroy this Reference Design, and furnish us a written confirmation to prove such destruction.

1. Restrictions on usage

1. This Reference Design is provided solely as reference data for designing electronics applications. Customers shall not use this Reference Design for any other purpose, including without limitation, verification of reliability.

2. This Reference Design is for customer's own use and not for sale, lease or other transfer.

3. Customers shall not use this Reference Design for evaluation in high or low temperature, high humidity, or high electromagnetic environments.

4. This Reference Design shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.

2. Limitations

 We reserve the right to make changes to this Reference Design without notice.
This Reference Design should be treated as a reference only. We are not responsible for any incorrect or incomplete data and information.

3. Semiconductor devices can malfunction or fail. When designing electronics applications by referring to this Reference Design, customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of semiconductor devices could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Customers must also

refer to and comply with the latest versions of all relevant our information, including without limitation, specifications, data sheets and application notes for semiconductor devices, as well as the precautions and conditions set forth in the "Semiconductor Reliability Handbook".

4. When designing electronics applications by referring to this Reference Design, customers must evaluate the whole system adequately. Customers are solely responsible for all aspects of their own product design or applications. WE ASSUME NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS. 5. No responsibility is assumed by us for any infringement of patents or any other intellectual property rights of third parties that may result from the use of this Reference Design. No license to any intellectual property right is granted by this terms of use, whether express or implied, by estoppel or otherwise. 6. THIS REFERENCE DESIGN IS PROVIDED "AS IS". WE (a) ASSUME NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (b) DISCLAIM ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO THIS REFERENCE DESIGN, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.

3. Export Control

Customers shall not use or otherwise make available this Reference Design for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). This Reference Design may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of this Reference Design are strictly prohibited except in compliance with all applicable export laws and regulations.

4. Governing Laws

This terms of use shall be governed and construed by laws of Japan.