

DCL52xx00

DCL520C00 / DCL520D00 / DCL521C00 / DCL521D00

1. Applications

- Industrial automation systems
- Motor control
- Inverter
- Switching power supply

2. Description

DCL520C00/DCL520D00/DCL521C00/DCL521D00 are dual-channel digital isolators based on Toshiba complementary metal-oxide semiconductor (CMOS) technology. High reinforced insulation is achieved by Toshiba CMOS technology and the magnetic coupling structure.

DCL520C00/DCL520D00/DCL521C00/DCL521D00 data channels are available in a variety of configuration with a withstand voltage of 3000 Vrms.

DCL520C00/DCL520D00/DCL521C00/DCL521D00 can operate with a temperature range of -40 to 125 °C and a wide supply voltage of 2.25 to 5.5 V.

3. Features

Data rate	: Up to 150 Mbps
Supply voltage	: 2.25 V to 5.5 V
Temperature Range	: -40 °C to 125 °C
Propagation Delay	: 10.9 ns Typical (5.0 V operation)
Default Output	: High and Low Options
High CMTI(typ)	: 100 kV/μs
Withstand Voltage	: 3.0 kVrms
Package	: SOIC8-N

Safety-Related Certification :

UL	: UL1577, File No. E519997
cUL	: CSA Component Acceptance Service Notice No. 5A, File No. E519997
VDE	: DIN EN IEC 60747-17 (VDE V 0884-17) (Planning)
CQC	: (Planning)


Note 1: When a VDE approved type is needed, please contact your Toshiba sales representative.

Start of commercial production
2025-08

Table of Contents


1. Applications	1
2. Description	1
3. Features	1
4. Internal Circuit (Simplified Schematic).....	3
5. Pin configuration and Functions.....	3
5.1. Pin Functions	3
6. Functional Description.....	4
7. Absolute Maximum Ratings ($T_a = 25\text{ }^{\circ}\text{C}$)	5
8. Recommended Operating Conditions (Note).....	5
9. Electrical Characteristics	6
9.1. Electrical Characteristics – 5 V Supply.....	6
9.2. Electrical Characteristics – 3.3 V Supply	7
9.3. Electrical Characteristics – 2.5 V Supply	8
9.4. Supply Current Characteristics – 5 V Supply	9
9.5. Supply Current Characteristics – 3.3 V Supply	10
9.6. Supply Current Characteristics – 2.5 V Supply	11
10. Insulation Specifications	12
11. Safety Limiting Values.....	13
12. Test Circuit	14
13. Characteristics Curves.....	18
14. Application Note	20
14-1. Eye diagram	20
14-2. PCB layout.....	20
15. Package Information.....	21
RESTRICTIONS ON PRODUCT USE	22

4. Internal Circuit (Simplified Schematic)




5. Pin configuration and Functions

DCL520C00 / DCL520D00



DCL521C00 / DCL521D00



5.1. Pin Functions

NAME	PIN		I/O	DESCRIPTION
	DCL520C00 DCL520D00	DCL521C00 DCL521D00		
VDD1	1	1	—	Power Supply, side 1
VI1	2	7	I	Input, Channel1
VI2	3	3	I	Input, Channel2
GND1	4	4	—	GND connection for VDD1, side 1
GND2	5	5	—	GND connection for VDD2, side 2
VO2	6	6	O	Output, Channel2
VO1	7	2	O	Output, Channel1
VDD2	8	8	—	Power Supply, side 2

6. Functional Description

(1) DCL520C00/ DCL520D00

V _{DDI}	V _{DDO}	INPUT (V _{IX})	OUTPUT (V _{Ox})	COMMENTS
PU	PU (Note1)	L	L	Normal Operation
		H	H	
		OPEN	Default	Default mode: When INPUT is open, the corresponding channel output goes to its default logic status. DCL520C00=L, DCL520D00=H
PD		L or OPEN		
PU	PD	X	Undetermined	When VDD ₂ is unpowered, a channel output is undetermined.
PD		L or OPEN		
PD	X	H	-	Don't use, since a certain voltage will be output through the internal ESD circuit.

PU= Powered up (VDD≥2.25 V), PD=Powered down (VDD≤1.7 V), H=High Level, L=Low Level, X=don't care

Note1 : The state of the output pin is fixed after 20μs from the time the power supply voltage V_{DDO} is turned on(PD⇒PU).

(2) DCL521C00/ DCL521D00

V _{DDI}	V _{DDO}	INPUT (V _{IX})	OUTPUT (V _{Ox})	COMMENTS
PU	PU (Note1)	L	L	Normal Operation
		H	H	
		OPEN	Default	Default mode: When INPUT is open, the corresponding channel output goes to its default logic status. DCL521C00=L, DCL521D00=H
PD		L or OPEN		
PU	PD	X	Undetermined	When VDD ₂ is unpowered, a channel output is undetermined.
PD		L or OPEN		
PD	X	H	-	Don't use, since a certain voltage will be output through the internal ESD circuit.

PU= Powered up (VDD≥2.25 V), PD=Powered down (VDD≤1.7 V), H=High Level, L=Low Level, X=don't care

Note1 : The state of the output pin is fixed after 20μs from the time the power supply voltage V_{DDO} is turned on(PD⇒PU).

7. Absolute Maximum Ratings ($T_a = 25\text{ }^{\circ}\text{C}$)

PARAMETER	SYMBOL	MIN	MAX	UNIT
Power supply voltage	V_{DD1}, V_{DD2}	-0.5	6.0	V
Input Voltage	V_I	-0.5	$V_{DD1}+0.5$ (Note1)	V
Output Voltage	V_O	-0.5	$V_{DD2}+0.5$ (Note1)	V
Output Current	I_O	-15	15	mA
Storage Temperature	T_{stg}	-65	150	$^{\circ}\text{C}$
Operating Temperature	T_{opr}	-40	125	$^{\circ}\text{C}$
Soldering Temperature (10 s)	T_{sol}	—	260	$^{\circ}\text{C}$
Maximum Withstanding Isolation Voltage (60 s)	BV_S	—	3000	Vrms

Note1: Maximum voltage must not exceed 6 V.

8. Recommended Operating Conditions (Note)

PARAMETER	SYMBOL	MIN	MAX	UNIT
Power supply voltage	V_{DD1}, V_{DD2}	2.25	5.5	V
Junction Temperature	T_J	-40	150	$^{\circ}\text{C}$
Ambient Temperature	T_a	-40	125	$^{\circ}\text{C}$

Note: The recommended operating conditions are given as a design guide necessary to obtain the intended performance of the device. Each parameter is an independent value. When creating a system design using this device, the electrical characteristics specified in this data sheet should also be considered.

Note: A ceramic capacitor (0.1 μF) should be connected between pin 1 (V_{DD1}) and pin 4 (GND_1) for V_{DD1} and between pin 8 (V_{DD2}) and pin 7 (GND_2) for V_{DD2} , and should be the layout on the IC as close as possible (less than 10 mm). Otherwise, the IC may not switch properly.

9. Electrical Characteristics

9.1. Electrical Characteristics – 5 V Supply

All typical specifications are at $T_a=25\text{ }^{\circ}\text{C}$, $V_{DD1}=V_{DD2}=5\text{ V}$. Minimum/maximum specifications apply over the entire recommended operating range of $4.5\text{ V}\leq V_{DD1}\leq 5.5\text{ V}$, $4.5\text{ V}\leq V_{DD2}\leq 5.5\text{ V}$, and $-40\text{ }^{\circ}\text{C}\leq T_a\leq 125\text{ }^{\circ}\text{C}$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	Fig.	SYMBOL	MIN	TYP.	MAX	UNIT
DC SPECIFICATIONS							
Under voltage Lockout	Threshold when supply voltage is rising	12-1	V_{DDxUV+}	—	2.1	2.25	V
	Threshold when supply voltage is falling		V_{DDxUV-}	1.7	1.9	—	
	Supply voltage hysteresis		V_{DDxUVH}	0.1	0.2	—	
Output Voltage Logic High	$V_{Ix}=H$, $I_{OH}=-20\text{ }\mu\text{A}$	12-2	V_{OH}	$V_{DDO}-0.1$ (Note1)	V_{DDO} (Note1)	—	V
	$V_{Ix}=H$, $I_{OH}=-4\text{ mA}$			$V_{DDO}-0.4$ (Note1)	$V_{DDO}-0.2$ (Note1)	—	
Output Voltage Logic Low	$V_{Ix}=L$, $I_{OL}=20\text{ }\mu\text{A}$	12-2	V_{OL}	—	0	0.1	V
	$V_{Ix}=L$, $I_{OL}=4\text{ mA}$			—	0.2	0.4	
Output impedance	—	12-2	Z_O	—	50	—	Ω
High-level input voltage	—	12-3	V_{IH}	$0.7\cdot V_{DDI}$ (Note1)	—	—	V
Low-level input voltage	—	12-3	V_{IL}	—	—	$0.3\cdot V_{DDI}$ (Note1)	V
Input Voltage Hysteresis	—	12-3	V_{HYS}	—	0.37	—	V
Input Current	$V_I=V_{DDI}$ (Note1) or 0 V	-	I_I	—	—	± 10	μA
SWITCHING SPECIFICATIONS							
Data Rate	—	-	t_{bps}	DC	—	150	Mbps
Pulse Width	—	-	PW	6.6	—	—	ns
Propagation Delay	50 kHz, Duty=50 %, $t_r=t_f=2\text{ ns}$, $C_L=15\text{ pF}$	12-4	t_{PHL} , t_{PLH}	—	10.9	18.3	ns
Pulse Width Distortion	$ t_{PHL} - t_{PLH} $	12-4	PWD	—	0.8	2.5	ns
Propagation Delay Skew (Between any two units)(Note2)	—	-	$t_{PSK(PP)}$	—	—	10	ns
Channel Matching	Same Direction	12-4	t_{skCD}	—	—	3.2	ns
	Opposing Direction	12-4	t_{skOD}	—	—	3.6	ns
Output Rise Time	10 % - 90 %	12-4	t_r	—	0.9	—	ns
Output Fall Time	90 % - 10 %	12-4	t_f	—	0.9	—	ns
Common mode transient Immunity	$V_I=V_{DDI}$ or 0 V , $V_{CM}=1500\text{ V}$, $T_a=25\text{ }^{\circ}\text{C}$	12-5	CMTI	—	100	—	kV/ μs

Note1: V_{DDI} =Input-side V_{DDx} , V_{DDO} =Output-side V_{DDx}

Note2: The propagation delay skew, t_{psk} , is equal to the magnitude of the difference in propagation delay that will be seen between units at the same given conditions (supply voltage, input current, temperature, etc.).

9.2. Electrical Characteristics – 3.3 V Supply

All typical specifications are at $T_a=25\text{ }^{\circ}\text{C}$, $V_{DD1}=V_{DD2}=3.3\text{ V}$. Minimum/maximum specifications apply over the entire recommended operating range of $3.0\text{ V}\leq V_{DD1}\leq 3.6\text{ V}$, $3.0\text{ V}\leq V_{DD2}\leq 3.6\text{ V}$, and $-40\text{ }^{\circ}\text{C}\leq T_a\leq 125\text{ }^{\circ}\text{C}$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	Fig.	SYMBOL	MIN	TYP.	MAX	UNIT
DC SPECIFICATIONS							
Under voltage Lockout	Threshold when supply voltage is rising	12-1	V_{DDxUV+}	—	2.1	2.25	V
	Threshold when supply voltage is falling		V_{DDxUV-}	1.7	1.9	—	
	Supply voltage hysteresis		V_{DDxUVH}	0.1	0.2	—	
Output Voltage Logic High	$V_{Ix}=H$, $I_{OH}=-20\text{ }\mu\text{A}$	12-2	V_{OH}	$V_{DDO}-0.1$ (Note1)	V_{DDO} (Note1)	—	V
	$V_{Ix}=H$, $I_{OH}=-4\text{ mA}$			$V_{DDO}-0.4$ (Note1)	$V_{DDO}-0.2$ (Note1)	—	
Output Voltage Logic Low	$V_{Ix}=L$, $I_{OL}=20\text{ }\mu\text{A}$	12-2	I_{OL}	—	0	0.1	V
	$V_{Ix}=L$, $I_{OL}=4\text{ mA}$			—	0.2	0.4	
Output impedance	—	12-2	Z_O	—	50	—	Ω
High-level input voltage	—	12-3	V_{IH}	$0.7\cdot V_{DDI}$ (Note1)	—	—	V
Low-level input voltage	—	12-3	V_{IL}	—	—	$0.3\cdot V_{DDI}$ (Note1)	V
Input Voltage Hysteresis	—	12-3	V_{HYS}	—	0.32	—	V
Input Current	$V_I=V_{DDI}$ (Note1) or 0 V	-	I_I	—	—	± 10	μA
SWITCHING SPECIFICATIONS							
Data Rate	—	-	t_{bps}	DC	—	150	Mbps
Pulse Width	—	-	PW	6.6	—	—	ns
Propagation Delay	50 kHz, Duty=50 %, $t_r=t_f=2\text{ ns}$, $C_L=15\text{ pF}$	12-4	t_{PHL} , t_{PLH}	—	11.6	19.1	ns
Pulse Width Distortion	$ t_{PHL} - t_{PLH} $	12-4	PWD	—	0.8	2.5	ns
Propagation Delay Skew (Between any two units)(Note2)	—	-	$t_{PSK(PP)}$	—	—	10	ns
Channel Matching	Same Direction	12-4	t_{skCD}	—	—	3.3	ns
	Opposing Direction	12-4	t_{skOD}	—	—	3.7	ns
Output Rise Time	10 % - 90 %	12-4	t_r	—	0.8	—	ns
Output Fall Time	90 % - 10 %	12-4	t_f	—	0.8	—	ns
Common mode transient Immunity	$V_I=V_{DDI}$ or 0 V , $V_{CM}=1500\text{ V}$, $T_a=25\text{ }^{\circ}\text{C}$	12-5	CMTI	—	100	—	kV/ μs

Note1: V_{DDI} =Input-side V_{DDx} , V_{DDO} =Output-side V_{DDx}

Note2: The propagation delay skew, t_{psk} , is equal to the magnitude of the difference in propagation delay that will be seen between units at the same given conditions (supply voltage, input current, temperature, etc.)

9.3. Electrical Characteristics – 2.5 V Supply

All typical specifications are at $T_a=25\text{ }^{\circ}\text{C}$, $V_{DD1}=V_{DD2}=2.5\text{ V}$. Minimum/maximum specifications apply over the entire recommended operating range of $2.25\text{ V}\leq V_{DD1}\leq 2.75\text{ V}$, $2.25\text{ V}\leq V_{DD2}\leq 2.75\text{ V}$, and $-40\text{ }^{\circ}\text{C}\leq T_a\leq 125\text{ }^{\circ}\text{C}$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	Fig.	SYMBOL	MIN	TYP.	MAX	UNIT
DC SPECIFICATIONS							
Under voltage Lockout	Threshold when supply voltage is rising	12-1	V_{DDxUV+}	—	2.1	2.25	V
	Threshold when supply voltage is falling		V_{DDxUV-}	1.7	1.9	—	
	Supply voltage hysteresis		V_{DDxUVH}	0.1	0.2	—	
Output Voltage Logic High	$V_{Ix}=H$, $I_{OH}=-20\text{ }\mu\text{A}$	12-2	V_{OH}	$V_{DDO}-0.1$ (Note1)	V_{DDO} (Note1)	—	V
	$V_{Ix}=H$, $I_{OH}=-4\text{ mA}$			$V_{DDO}-0.4$ (Note1)	$V_{DDO}-0.2$ (Note1)	—	
Output Voltage Logic Low	$V_{Ix}=L$, $I_{OL}=20\text{ }\mu\text{A}$	12-2	I_{OL}	—	0	0.1	V
	$V_{Ix}=L$, $I_{OL}=4\text{ mA}$			—	0.2	0.4	
Output impedance	—	12-2	Z_O	—	50	—	Ω
High-level input voltage	—	12-3	V_{IH}	$0.7\cdot V_{DDI}$ (Note1)	—	—	V
Low-level input voltage	—	12-3	V_{IL}	—	—	$0.3\cdot V_{DDI}$ (Note1)	V
Input Voltage Hysteresis	—	12-3	V_{HYS}	—	0.32	—	V
Input Current	$V_I=V_{DDI}$ (Note1) or 0 V	-	I_I	—	—	± 10	μA
SWITCHING SPECIFICATIONS							
Data Rate	—	-	t_{bps}	DC	—	150	Mbps
Pulse Width	—	-	PW	6.6	—	—	ns
Propagation Delay	50 kHz, Duty=50 %, $t_r=t_f=2\text{ ns}$, $C_L=15\text{ pF}$	12-4	t_{PHL} , t_{PLH}	—	12.6	21.0	ns
Pulse Width Distortion	$ t_{PHL} - t_{PLH} $	12-4	PWD	—	1.0	2.5	ns
Propagation Delay Skew (Between any two units)(Note2)	—	-	$t_{PSK(PP)}$	—	—	10	ns
Channel Matching	Same Direction	12-4	t_{skCD}	—	—	3.5	ns
	Opposing Direction	12-4	t_{skOD}	—	—	3.9	ns
Output Rise Time	10 % - 90 %	12-4	t_r	—	0.8	—	ns
Output Fall Time	90 % - 10 %	12-4	t_f	—	0.8	—	ns
Common mode transient Immunity	$V_I=V_{DDI}$ or 0 V , $V_{CM}=1500\text{ V}$, $T_a=25\text{ }^{\circ}\text{C}$	12-5	CMTI	—	100	—	kV/ μs

Note1: V_{DDI} =Input-side V_{DDx} , V_{DDO} =Output-side V_{DDx}

Note2: The propagation delay skew, t_{psk} , is equal to the magnitude of the difference in propagation delay that will be seen between units at the same given conditions (supply voltage, input current, temperature, etc.)

9.4. Supply Current Characteristics – 5 V Supply

All typical specifications are at $T_a=25\text{ }^{\circ}\text{C}$, $V_{DD1}=V_{DD2}=5\text{ V}$. Minimum/maximum specifications apply over the entire recommended operating range of $4.5\text{ V}\leq V_{DD1}\leq 5.5\text{ V}$, $4.5\text{ V}\leq V_{DD2}\leq 5.5\text{ V}$, and $-40\text{ }^{\circ}\text{C}\leq T_a\leq 125\text{ }^{\circ}\text{C}$, unless otherwise noted.

(1) DCL520X00

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Current (DC Signal)	$V_I=0$ (DCL520C00), $V_I=1$ (DCL520D00)	$I_{DD1(Q)}$	—	1.1	1.7	mA
		$I_{DD2(Q)}$	—	2.6	4	mA
	$V_I=0$ (DCL520D00), $V_I=1$ (DCL520C00)	$I_{DD1(Q)}$	—	10.5	16	mA
		$I_{DD2(Q)}$	—	2.9	4.3	mA
1 Mbps	$f_{CLK}=500\text{ kHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(1)}$	—	5.9	9.2	mA
		$I_{DD2(1)}$	—	2.8	4.4	mA
25 Mbps	$f_{CLK}=12.5\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(25)}$	—	5.9	8.7	mA
		$I_{DD2(25)}$	—	5.2	7.4	mA
100 Mbps	$f_{CLK}=50\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(100)}$	—	6.9	9.6	mA
		$I_{DD2(100)}$	—	14	19.4	mA

(2) DCL521X00

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Current (DC Signal)	$V_I=0$ (DCL521C00), $V_I=1$ (DCL521D00)	$I_{DD1(Q)}$	—	2.0	3.0	mA
		$I_{DD2(Q)}$	—	2.0	3.0	mA
	$V_I=0$ (DCL521D00), $V_I=1$ (DCL521C00)	$I_{DD1(Q)}$	—	7.2	10.4	mA
		$I_{DD2(Q)}$	—	7.2	10.4	mA
1 Mbps	$f_{CLK}=500\text{ kHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(1)}$	—	4.6	6.8	mA
		$I_{DD2(1)}$	—	4.6	6.8	mA
25 Mbps	$f_{CLK}=12.5\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(25)}$	—	6.1	8.5	mA
		$I_{DD2(25)}$	—	6.1	8.5	mA
100 Mbps	$f_{CLK}=50\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(100)}$	—	11.1	15.6	mA
		$I_{DD2(100)}$	—	11.1	15.6	mA

9.5. Supply Current Characteristics – 3.3 V Supply

All typical specifications are at $T_a=25^\circ\text{C}$, $V_{DD1}=V_{DD2}=3.3\text{ V}$. Minimum/maximum specifications apply over the entire recommended operating range of $3.0\text{ V}\leq V_{DD1}\leq 3.6\text{ V}$, $3.0\text{ V}\leq V_{DD2}\leq 3.6\text{ V}$, and $-40^\circ\text{C}\leq T_a\leq 125^\circ\text{C}$, unless otherwise noted.

(1) DCL520X00

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Current (DC Signal)	$V_I=0(\text{DCL520C00})$, $V_I=1(\text{DCL520D00})$	$I_{DD1(Q)}$	—	1.1	1.5	mA
		$I_{DD2(Q)}$	—	2.6	3.8	mA
	$V_I=0(\text{DCL520D00})$, $V_I=1(\text{DCL520C00})$	$I_{DD1(Q)}$	—	10.4	15.5	mA
		$I_{DD2(Q)}$	—	2.8	4.2	mA
1 Mbps	$f_{CLK}=500\text{ kHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(1)}$	—	5.7	9	mA
		$I_{DD2(1)}$	—	2.7	4.2	mA
25 Mbps	$f_{CLK}=12.5\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(25)}$	—	5.7	8.3	mA
		$I_{DD2(25)}$	—	4.4	6.4	mA
100 Mbps	$f_{CLK}=50\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(100)}$	—	6.5	8.9	mA
		$I_{DD2(100)}$	—	9.2	15.7	mA

(2) DCL521X00

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Current (DC Signal)	$V_I=0(\text{DCL521C00})$, $V_I=1(\text{DCL521D00})$	$I_{DD1(Q)}$	—	2.0	2.8	mA
		$I_{DD2(Q)}$	—	2.0	2.8	mA
	$V_I=0(\text{DCL521D00})$, $V_I=1(\text{DCL521C00})$	$I_{DD1(Q)}$	—	7.1	10.2	mA
		$I_{DD2(Q)}$	—	7.1	10.2	mA
1 Mbps	$f_{CLK}=500\text{ kHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(1)}$	—	4.5	6.6	mA
		$I_{DD2(1)}$	—	4.5	6.6	mA
25 Mbps	$f_{CLK}=12.5\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(25)}$	—	5.5	7.6	mA
		$I_{DD2(25)}$	—	5.5	7.6	mA
100 Mbps	$f_{CLK}=50\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(100)}$	—	8.7	12.3	mA
		$I_{DD2(100)}$	—	8.7	12.3	mA

9.6. Supply Current Characteristics – 2.5 V Supply

All typical specifications are at $T_a=25^\circ\text{C}$, $V_{DD1}=V_{DD2}=2.5\text{ V}$. Minimum/maximum specifications apply over the entire recommended operating range of $2.25\text{ V}\leq V_{DD1}\leq 2.75\text{ V}$, $2.25\text{ V}\leq V_{DD2}\leq 2.75\text{ V}$, and $-40^\circ\text{C}\leq T_a\leq 125^\circ\text{C}$, unless otherwise noted.

(1) DCL520X00

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Current (DC Signal)	$V_I=0$ (DCL520C00), $V_I=1$ (DCL520D00)	$I_{DD1(Q)}$	—	0.98	1.5	mA
		$I_{DD2(Q)}$	—	2.52	3.7	mA
	$V_I=0$ (DCL520D00), $V_I=1$ (DCL520C00)	$I_{DD1(Q)}$	—	10.4	15.4	mA
		$I_{DD2(Q)}$	—	2.8	4.1	mA
1 Mbps	$f_{CLK}=500\text{ kHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(1)}$	—	5.6	8.8	mA
		$I_{DD2(1)}$	—	2.7	4.1	mA
25 Mbps	$f_{CLK}=12.5\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(25)}$	—	5.5	8	mA
		$I_{DD2(25)}$	—	4	5.9	mA
100 Mbps	$f_{CLK}=50\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(100)}$	—	6.4	8.4	mA
		$I_{DD2(100)}$	—	7.5	13.3	mA

(2) DCL521X00

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Current (DC Signal)	$V_I=0$ (DCL521C00), $V_I=1$ (DCL521D00)	$I_{DD1(Q)}$	—	1.9	2.8	mA
		$I_{DD2(Q)}$	—	1.9	2.8	mA
	$V_I=0$ (DCL521D00), $V_I=1$ (DCL521C00)	$I_{DD1(Q)}$	—	7.1	10.1	mA
		$I_{DD2(Q)}$	—	7.1	10.1	mA
1 Mbps	$f_{CLK}=500\text{ kHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(1)}$	—	4.4	6.5	mA
		$I_{DD2(1)}$	—	4.4	6.5	mA
25 Mbps	$f_{CLK}=12.5\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(25)}$	—	5.2	7.2	mA
		$I_{DD2(25)}$	—	5.2	7.2	mA
100 Mbps	$f_{CLK}=50\text{ MHz}$, duty=50 % cycle square wave. $C_L=15\text{ pF}$	$I_{DD1(100)}$	—	7.6	10.9	mA
		$I_{DD2(100)}$	—	7.6	10.9	mA

10. Insulation Specifications

PARAMETER	Symbol	TEST CONDITIONS	VALUE	UNIT
Minimum External Clearance	CLR	—	4.0	mm
Minimum External Creepage	CPG	—	3.8	mm
Distance Through The Insulation	DTI	—	17	μm
Comparative Tracking Index	CTI	—	400	V
Material Group	—	According to IEC 60664-1	II	—
Overvoltage Category Per IEC 60664-1	—	Related Mains Voltage ≤ 150 V _{RMS}	I-IV	—
	—	Related Mains Voltage ≤ 300 V _{RMS}	I-III	—
DIN EN IEC 60747-17; EN IEC 60747-17				
Maximum Repetitive Peak Isolation Voltage	V _{IORM}	AC voltage (bipolar)	566	V _{PK}
Maximum Transient Isolation Voltage	V _{IOTM}	V _{TEST} = V _{IOTM} , t = 60 s (qualification) , V _{TEST} = 1.2 × V _{IOTM} , t = 1 s (100 % production)	4243	V _{PK}
Maximum Impulse Voltage	V _{IMP}	IEC 62368-1 1.2/50 μs waveform	5000	V _{PK}
Maximum surge isolation Voltage	V _{IOSM}	Test method per IEC 62368-1, 1.2/50 μs waveform, V _{TEST} ≥ 1.3 × V _{IMP} (qualification) , min.10 kV	10000	V _{PK}
Apparent charge measuring voltage	V _{pd(m)}	Method A, After Input/Output safety test subgroup2&3, V _{IORM} × 1.2 = V _{pd} (m), t _{ini} = 60 sec, t _m = 10 sec, partial discharge < 5 pC	679	V _{PK}
		Method A, After environmental tests subgroup 1, V _{IORM} × 1.6 = V _{pd} (m), t _{ini} = 60 sec, t _m = 10 sec, partial discharge < 5 pC	906	
		Method B2; At routine test (100 % production) and preconditioning (type test) V _{IORM} × 1.875 = V _{pd} (m), 100 % production test, t _{ini} = t _m = 1 sec, partial discharge < 5 pC	1062	
Barrier capacitance, input to output	C _{IO}	f = 1 MHz	0.8	pF
Input Capacitance	C _I	V _{Ix}	1.9	pF
Isolation Resistance	R _{IO}	V _{IO} = 500 V, T _A = 25 °C	>10 ¹²	Ω
		V _{IO} = 500 V, 100 °C ≤ T _A ≤ 125 °C	≥10 ¹¹	
		V _{IO} = 500 V at T _S = 150 °C	≥10 ⁹	
Pollution Degree	—	—	2	—
Climatic Category	—	—	40/125/21	—
UL 1577				
Maximum Withstanding Isolation Voltage	V _{ISO}	V _{TEST} = V _{ISO} , t = 60 s (qualification), V _{TEST} = 1.2 × V _{ISO} , t = 1 s (100 % production)	3000	V _{RMS}

11. Safety Limiting Values

PARAMETER	Symbol	TEST CONDITIONS	Value	Unit
Safety Input, Output Or Supply Current	I _S	V _{DD1} =V _{DD2} =5.5 V, T _j =150 °C, T _a =25 °C	255	mA
		V _{DD1} =V _{DD2} =3.6 V, T _j =150 °C, T _a =25 °C	390	mA
		V _{DD1} =V _{DD2} =2.75 V, T _j =150 °C, T _a =25 °C	510	mA
Safety Input, Output Or Total Power	P _S	T _j =150 °C, T _a =25 °C	1403	W
Maximum Safety Temperature	T _S	-	150	°C






Fig. 11.1 Thermal Derating Curve for Safety Limiting Current— T_a

12. Test Circuit




1: Default=L : V_{DD} , Default=H : GND

Fig. 12.1.1 DCL520C00/DCL520D00 V_{DD1UV+} / V_{DD1UV-} Test Circuit




1: Default=L : V_{DD} , Default=H : GND

Fig. 12.1.2 DCL521C00/DCL521D00 V_{DD1UV+} / V_{DD1UV-} Test Circuit



1: Default=L : V_{DD} , Default=H : GND

Fig. 12.1.3 DCL520C00/DCL520D00 V_{DD2UV+} / V_{DD2UV-} Test Circuit



1: Default=L : V_{DD} , Default=H : GND

Fig. 12.1.4 DCL521C00/DCL521D00 V_{DD2UV+} / V_{DD2UV-} Test Circuit




Fig. 12.2.1 DCL520C00/DCL520D00 V_{OH}/V_{OL} Test Circuit




Fig. 12.2.2 DCL521C00/DCL521D00 V_{OH}/V_{OL} Test Circuit




Fig. 12.3.1 DCL520C00/DCL520D00 V_{IH}/V_{IL} Test Circuit






Fig. 12.3.2 DCL521C00/DCL521D00 V_{IH}/V_{IL} Test Circuit



- 1: The input pulse is supplied by a generator having the following characteristics: PRR $\leq$ 50 kHz, 50 % duty cycle, $t_r \leq 2$ ns, $t_f \leq 2$ ns, $Z_0 = 50 \Omega$. At the input, 50 Ω resistor is required to terminate input generator signal. It is needed not in actual application.
- 2: $CLx=15$ pF includes instrumentation and fixture capacitance.

Fig.12.4.1 DCL520C00/DCL520D00 Switching Test Circuit



- 1: The input pulse is supplied by a generator having the following characteristics: PRR $\leq$ 50 kHz, 50 % duty cycle, $t_r \leq 2$ ns, $t_f \leq 2$ ns, $Z_0 = 50 \Omega$. At the input, 50 Ω resistor is required to terminate input generator signal. It is needed not in actual application.
- 2: $CLx=15$ pF includes instrumentation and fixture capacitance.

Fig.12.4.2 DCL521C00/DCL521D00 Switching Test Circuit






Fig.12.4.3 Switching Test Circuit and Voltage Waveforms



1: CLx=15 pF includes instrumentation and fixture capacitance.

Fig.12.5.1 DCL520C00/DCL520D00 Common-Mode Transient Immunity Test Circuit



1: CLx=15 pF includes instrumentation and fixture capacitance.

Fig.12.5.2 DCL521C00/DCL521D00 Common-Mode Transient Immunity Test Circuit

13. Characteristics Curves

Note: The following characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.




Fig.13.1 DCL520x00 I_{DD1} Supply Current–Data rate




Fig.13.2 DCL520xx00 I_{DD2} Supply Current–Data rate




Fig.13.3 DCL521x00 I_{DD1} Supply Current–Data rate




Fig.13.4 DCL521xx00 I_{DD2} Supply Current–Data rate




Fig.13.5 VOH-IOH




Fig.13.6 VOL-IOL




Fig.13.7 Propagation Delay Time t_{pHL} - T_a




Fig.13.8 Propagation Delay Time t_{pLH} - T_a

14. Application Note

14-1. Eye diagram

The following figure shows typical eye diagrams of DCL521xx00 at the maximum data rate of 150 Mbps with pseudorandom bit sequences (PRBS), supply voltage 3.0V for reference only.




Fig.14.1 DCL521xx00 Eye diagram at 150Mbps

14-2. PCB layout

A ceramic capacitor (0.1 μ F) should be connected between pin 1 (V_{DD1}) and pin 2 (GND_1) for V_{DD1} and between pin 16 (V_{DD2}) and pin 15 (GND_2) for V_{DD2} , and it should be the layout on the IC as close as possible (less than 10mm). Otherwise, the IC may not operate properly.








Fig.14.2 Recommended Printed Circuit Board Layout

15. Package Information

Implementation category	Surface Mount
Pin Number	8
Weight (g)	0.07 (Typical)
Package Dimension (mm) Width × Length × Height	4.9 × 6.0 × 1.75 (Max)
Package Dimension (mm)	 
Land Pattern Example (mm) [for reference only]	 Nominal  Optional Large interval between primary-secondary side

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, lifesaving and/or life supporting medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, and devices related to power plant. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**