

Application Note

UART_TRANS

Arm and Keil are registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere.

All other company names, product names, and service names mentioned herein may be trademarks of their respective companies.

Table of Contents

Table of Contents	2
1. Preface	3
2. Technical Term	3
3. Reference Document	3
4. Target Sample Program	4
5. Configuration Diagram	4
6. Sample Program: UART_TRANS	5
6.1. Outlines of Operation	5
6.2. Function to Use	5
6.3. Interrupt to Use	5
6.4. Configuration	5
6.5. Example of Terminal Emulator Output	6
6.6. How to switch DMAC function	7
6.6.1. IAR Embedded Workbench	7
6.6.2. Keil µVision	9
6.6.3. SEGGER Embedded Studio	11
6.7. DMAC Communication Setting	13
7. Activity diagram	14
7.1. main	14
7.2. Interrupt	16
8. Revision History	17
RESTRICTIONS ON PRODUCT USE	18

1. Preface

This application note describes the sample software UART_TRANS using Universal Asynchronous Receiver Transmitter (UART).

This document helps the user check operation of a product under development and develop its program.

2. Technical Term

Term/Abbreviation	Definition
BSP	Board Support Package
CG	Clock Control and Operation Mode
DMA	Direct Memory Access Controller
Timer	T32A:32-bit Timer Event Counter
UART	Universal Asynchronous Receiver Transmitter


3. Reference Document

Document	Notes
Data sheet	Refer to the data sheet of MCU to be used.
Reference manual	Refer to the reference manual of each IP to be used.
Application note MCU User Guide	Refer to the MCU user guide to be used.

4. Target Sample Program

Sample Program	Outline
UART_TRANS	Sample program of UART communication function

5. Configuration Diagram



6. Sample Program: UART_TRANS

This sample software uses the transmission function of the UART communication function to send string 1 to the terminal software, triggered by pressing a switch, and turns the LED on/off with each UART transmission.

6.1. Outlines of Operation

Wait for BSP_PSW_1 to be pressed.

When BSP_PSW_1 is pressed, string 1 is sent via UART, BSP_LED_2 is turned on/off, and BSP_LED_3 is turned off.

If an error occurs, BSP_LED_3 is turned on.

6.2. Function to Use

The functions to use are as follows:

For the Port assignment of each BSP channel, refer to the MCU user guide.

IP	Channel	Objective
UART	BSP_UART_1	For terminal emulator communication
T32A	BSP_T32A_TIMER_1	Interval timer
PORT (Push-Switch)	BSP_PSW_1	Event Trigger
PORT (LED)	BSP_LED_2	For operation check
	BSP_LED_3	For operation check

6.3. Interrupt to Use

For details, please refer to the "Interrupt List by Sample" in the MCU User's Manual.

6.4. Configuration

Configuration setting.

Configuration	Soft Definition Name	Current Value (Defaults)	Description
String 1	BSP_MCU_NAME	(Note1)	Character string to send
Communication Control Selection	NODMAC PJ option	(Note2): NODMAC	NODMAC (Does not use DMAC), DMA (Use DMAC) Can be switched

Note1: Please refer to the "Log Control and Others" section in the MCU User's Manual.

Note2: For information on how to switch when using DMAC, see Chapter 6.6.

6.5. Example of Terminal Emulator Output


Outputs the sent character string

```
TMPM471F10  
TMPM471F10
```

6.6. How to switch DMAC function

Follow the steps below to enable/disable the DMAC function.



6.6.1. IAR Embedded Workbench



Change "Defined symbol" as follows:

If you do not use DMAC: "NODMAC"

When using DMAC: "DMA", "UART_DMA_TRANSFER_USE"



If you want to use the file, uncheck "Exclude from build", otherwise uncheck "Exclude from build".

DMAC disabled:


bsp_config_sbk_m4xx_dmac.c	Don't use files
bsp_config_sbk_m4xx_uart_io.c	Use files
bsp_config_sbk_m4xx_uart_io_dma.c	Don't use files

DMAC enabled:

bsp_config_sbk_m4xx_dmac.c	Use files
bsp_config_sbk_m4xx_uart_io.c	Don't use files
bsp_config_sbk_m4xx_uart_io_dma.c	Use files

Please build after changing the settings.

6.6.2. Keil µVision





Open "Project" > "Options for Target 'Sample'" > "C/C++".

Change "Define:" of "Preprocessor Symbols" as shown below.

If you do not use DMAC, select "NODMAC"

"DMA" and "UART_DMA_TRANSFER_USE" when using DMAC



Right-click the file you want to configure, open Options for File 'xxxx.c' and change "Include in Target Build". If you want to use the file, check "Include in Target Build", otherwise uncheck "Include in Target Build".

DMAC disabled:


bsp_config_sbk_m4xx_dmac.c	Don't use files
bsp_config_sbk_m4xx_uart_io.c	Use files
bsp_config_sbk_m4xx_uart_io_dma.c	Don't use files

DMAC enabled:

bsp_config_sbk_m4xx_dmac.c	Use files
bsp_config_sbk_m4xx_uart_io.c	Don't use files
bsp_config_sbk_m4xx_uart_io_dma.c	Use files

Please build after changing the settings.

6.6.3. SEGGER Embedded Studio




Open "Project" > "Options" > "Preprocessor".


Change "Preprocessor Definitions" as shown below.

If you do not use DMAC, select "NODMAC"

"DMA" and "UART_DMA_TRANSFER_USE" when using DMAC

Note: Change "Common" as well as "Sample_xxx".





Right-click the file you want to configure and change "Exclude From Build".

If you want to use a file, uncheck "Exclude From Build", otherwise check "Exclude From Build".

DMAC disabled:

bsp_config_sbk_m4xx_dmac.c	Don't use files
bsp_config_sbk_m4xx_uart_io.c	Use files
bsp_config_sbk_m4xx_uart_io_dma.c	Don't use files

DMAC enabled:

bsp_config_sbk_m4xx_dmac.c	Use files
bsp_config_sbk_m4xx_uart_io.c	Don't use files
bsp_config_sbk_m4xx_uart_io_dma.c	Use files

Please build after changing the settings.

6.7. DMAC Communication Setting

Startup Factors and Transfer Mode


Configuration	Description
Startup Factors	DMA Request from TSPI Driver (Request Based on FIFO level)
Transfer Mode	Singel Transfer/Unit Normal Transfer


Channel Control Data: Transfer Mode Setting [DMACHnICfg]

Configuration	Description
Destination Address Increment	00: [1byte]
Destination Data Size	00: [1byte]
Source Address Increment	11: [No increment]
Source Data Size	00: [1byte]
Arbitration	0000: [After 1 Rotation Transfer]
Transfer Count	0x000: [1time]
Singel Transfer Setting	0: [Not used because it is not a chain transfer]
Transfer Mode	001: [Unit Normal Transfer]


7. Activity diagram

7.1. main





7.2. Interrupt



8. Revision History

Revision	Date	Description
1.0	2025-01-20	First release
1.1	2025-10-30	6.3 Interrupt to Use Added M3H Interrupt Name.
1.2	2026-07-30	6.3 Interrupt to Use Detailed information is transcribed into the User's Manual

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, Class 3 medical devices, equipment used for automobiles, and military vehicles and munitions. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**